





1

DS-D



DS-E



Galvanized

Stainless

-40 - +80 °C

RoHS

3

4

5

6

2

d ₁	h	d ₂	l	t	s	D	E
15	14	M4	10	4	1,4	•	•
20	23,5	M6	18	6	2	•	•
25	18,5	M6	18	6	2	•	•
30	28,5	M8	20	8	2	•	•
40	28	M8	23	8	2	•	•
50	28	M10	28	10	2	•	•
70	43	M10	27	10	3	•	•
75	37	M12	37	12	3	•	•
100	50	M16	41	16	3	•	•

Appearance

- **Elastomer (default natural rubber, NK)**
 - Operation temperature -40 - +80 °C
 - Should not be used at oil, alkaline, acid
 - You can find other opportunities at the Elastomer

7

- **Hardness (default 55 +/-5 Shore A)**

- 43 (soft)
- 55 (medium)
- 72 (hard)

8

- **Metal insert**

- ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)
- A2 (stainless, AISI 304)
- A4 (stainless, AISI 316)

9

Use

Thanks for the special design this part is very useful for moving equipments, where you can not fix the part to its environments.

Concave vibration dumper

1 2 3 4 5 6 7 8 9
DS-D 100/50 M16x41 NK 55 +/-5 SH A, ST37

1	Product code
2	Type
3	Diameter (d ₁)
4	Height (h)
5	Thread size (d ₂)
6	Thread length (l)
7	Elastomer
8	Hardness
9	Metal quality