



- Galvanized
- Stainless
- 40 - +80 °C
- RoHS

3	4	5	6			2	
d ₁	h	d ₂	l	t	s	D	E
50	35	M10	28	10	2	•	•
80	60	M12	37	12	3	•	•
125	90	M16	41	16	3	•	•

Appearance

- Elastomer (default natural rubber, NK)**

 - Operation temperature -40 - +80 °C
 - Should not be used at oil, alkaline, acid
 - You can find other opportunities at the Elastomer

7
- Hardness (default 55 +/-5 Shore A)**

 - 43 (soft)
 - 55 (medium)
 - 72 (hard)

8
- Metal insert**

 - ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)
 - A2 (stainless, AISI 304)
 - A4 (stainless, AISI 316)

9

Use

These KE products are one of the group of the bumpers. These are perfect for the elastic end position storage. According to the small machines these products are perfect for their feet.

Radiused vibration dumper

1 2 3 4 5 6 7 8 9

KE-D 125/60 M16x41 NK 55 +/-5 SH A, ST37

1	Product group
2	Type
3	Diameter (d ₁)
4	Height (h)
5	Thread size (d ₂)
6	Thread length (l)
7	Elastomer
8	Hardness
9	Metal quality