



- Galvanized
- Stainless
- 40 - +80 °C
- RoHS

**3**

**4**

**5**

**6**

**2**

d <sub>1</sub>	h	d <sub>2</sub>	l	t	s	D	E
25	13	M6	18	6	2	•	•
25	15	M6	18	6	2	•	•
30	26	M8	20	8	2	•	•
50	30	M8	28	8	2	•	•

**Appearance**

- 7**

• **Elastomer (default natural rubber, NK)**

  - Operation temperature -40 - +80 °C
  - Should not be used at oil, alkaline, acid
  - You can find other opportunities at the Elastomer
- 8**

• **Hardness (default 55 +/-5 Shore A)**

  - 43 (soft)
  - 55 (medium)
  - 72 (hard)
- 9**

• **Metal insert**

  - ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)
  - A2 (stainless, AISI 304)
  - A4 (stainless, AISI 316)

**Use**

These KG products are one of the group of the bumpers. These are perfect for the elastic end position storage. According to the small machines these products are perfect for their feet.

**1 2 3 4 5 6 7 8 9**

KG-D 125/60 M16x41 NK 55 +/-5 SH A, ST37

<b>1</b>	Product group
<b>2</b>	Type
<b>3</b>	Diameter (d <sub>1</sub> )
<b>4</b>	Height (h)
<b>5</b>	Thread size (d <sub>2</sub> )
<b>6</b>	Thread length (l)
<b>7</b>	Elastomer
<b>8</b>	Hardness
<b>9</b>	Metal quality