


GS-M1




2 3

5

1

b	h	GS-M1			GS-M2		
		5	10	15	5	10	15
10	30	●	●	○	●	●	○
20	25	●	●	○	●	○	○
20	30	●	●	○	●	●	○
25	25	●	●	○	●	●	○
25	30	●	●	○	●	●	○
30	20	●	●	○	●	○	○
30	30	●	●	○	●	●	○
35	15	●	●	○	○	○	○
35	50	●	●	○	●	●	○
40	20	●	●	○	●	○	○
40	30	●	●	○	●	●	○
40	35	●	●	○	●	●	○
40	40	●	●	○	●	●	○
40	45	●	●	○	●	●	○
40	50	●	●	○	●	●	○
50	10	●	○	○	○	○	○
50	15	●	○	○	○	○	○
50	20	●	●	○	●	○	○
50	25	●	●	●	●	○	○
50	30	●	●	●	●	○	○
50	35	●	●	●	●	○	○
50	40	●	●	●	●	●	●
50	45	●	●	●	●	●	●

GS-M2



2 3

5

1

1

b	h	GS-M1			GS-M2		
		5	10	15	5	10	15
50	50	●	●	●	●	●	●
50	55	●	●	●	●	●	●
50	60	●	●	●	●	●	●
50	70	●	●	●	●	●	●
60	20	●	●	●	○	●	○
60	30	●	●	●	●	●	○
60	35	●	●	●	●	●	○
60	40	●	●	●	●	●	●
60	45	●	●	●	●	●	●
60	50	●	●	●	●	●	●
60	55	●	●	●	●	●	●
60	60	●	●	●	●	●	●
60	70	●	●	●	●	●	●
60	80	●	●	●	●	●	●
70	30	●	●	●	●	●	○
70	40	●	●	●	●	●	●
70	45	●	●	●	●	●	●
70	50	●	●	●	●	●	●
70	55	●	●	●	●	●	●
70	60	●	●	●	●	●	●
70	65	●	●	●	●	●	●
70	70	●	●	●	●	●	●
70	80	●	●	●	●	●	●

### Appearance

- Elastomer (default natural rubber, NK)**
  - Operation temperature -40 - +80 °C
  - Should not be used at oil, alkaline, acid
  - You can find other opportunities at the Elastomer
- Hardness (default 55 +/-5 Shore A)**
  - 43 (soft)
  - 55 (medium)
  - 72 (hard)
- Metal insert**
  - ST37 (painted black)
  - A2 (stainless, AISI 304)
  - A4 (stainless, AISI 316)



### Use

We produce wide range of rubber tracks.  
There are easy to cut for the proper size and form. They can be fixed by screw connection.

### Rubber track

1 Type  
2 Width (B)  
3 Height (H)  
4 Length  
5 Thickness (S)  
6 Elastomer  
7 Hardness  
8 Metal quality

GS-M1 50x50x2000 S=10 NK 55 +/-5 SH A, ST37



2 3

5

1

GS-M1

GS-M2

s

b	h	5	10	15	5	10	15
75	40	●	●	●	●	●	○
75	55	●	●	●	●	●	●
80	20	●	●	○	●	○	○
80	40	●	●	●	●	●	●
80	45	●	●	●	●	●	●
80	60	●	●	●	●	●	●
80	70	●	●	●	●	●	●
80	80	●	●	●	●	●	●
90	45	●	●	●	●	●	●
100	12	●	○	○	○	○	○
100	20	●	●	○	●	○	○
100	30	●	●	●	●	●	○
100	40	●	●	●	●	●	●
100	45	●	●	●	●	●	●
100	50	●	●	●	●	●	●
100	55	●	●	●	●	●	●
100	60	●	●	●	●	●	●
100	65	●	●	●	●	●	●
100	70	●	●	●	●	●	●
100	75	●	●	●	●	●	●
100	80	●	●	●	●	●	●
100	90	●	●	●	●	●	●
100	100	●	●	●	●	●	●

2

3

5

1

GS-M1 GS-M2

s

b	h	5	10	15	5	10	15
110	40	○	●	●	○	●	●
120	45	○	●	●	○	●	●
120	50	○	●	●	○	●	●
120	60	○	●	●	○	●	●
120	70	○	●	●	○	●	●
120	80	○	●	●	○	●	●
150	30	○	●	●	○	●	○
150	40	○	●	●	○	●	●
150	50	○	●	●	○	●	●
150	60	○	●	●	○	●	●
150	70	○	●	●	○	●	●
150	75	○	●	●	○	●	●
150	80	○	●	●	○	●	●
150	90	○	●	●	○	●	●
150	100	○	●	●	○	●	●
200	30	○	●	●	○	●	●
200	60	○	●	●	○	●	●
200	70	○	●	●	○	●	●
200	80	○	●	●	○	●	●
200	100	○	●	●	○	●	●

## Appearance

- Elastomer (default natural rubber, NK)**
  - Operation temperature -40 - +80 °C
  - Should not be used at oil, alkaline, acid
  - You can find other opportunities at the Elastomer
- Hardness (default 55 +/-5 Shore A)**
  - 43 (soft)
  - 55 (medium)
  - 72 (hard)
- Metal insert**
  - ST37 (painted black)
  - A2 (stainless, AISI 304)
  - A4 (stainless, AISI 316)

## Use

We produce wide range of rubber tracks.  
There are easy to cut for the proper size and form. They can be fixed by screw connection.

## Rubber track

1 Type  
2 Width(B)  
3 Height(H)  
4 Length  
5 Thickness (S)  
6 Elastomer  
7 Hardness  
8 Metal quality

GS-M1 50x50x2000 S=10 NK 55 +/- 5 SH A, ST37