



Galvanized

-40 - +80 °C

RoHS

1

Item code	$d_1$	h	$d_2$	l	L	SW
MFL-01	80	38 - 48	M12x1,5	100	75 - 65	8
MFL-02	120	43 - 50	M16x1,5	120	80 - 68	9
MFL-03	160	48 - 53	M20x1,5	170	125 - 110	12

Item code	Statikus terhelés [N]	Dinamikus terhelés [N]		
		200 ciklus/perc	160 ciklus/perc	<125 ciklus/perc
MFL-01	6 000	1 200	1 400	2 000
MFL-02	15 000	2 500	3 500	4 000
MFL-03	30 000	7 000	10 000	25 000

## Appearance

- **Elastomer (default natural rubber, NK)**
  - Operation temperature -40 - +80 °C
  - Should not be used at oil, alkaline, acid
  - You can find other opportunities at the Elastomer

2

- **Hardness (default 70 +/-5 Shore A)**

- 40 (soft)
- 55 (medium)
- 70 (hard)

3

- **Metal insert**

- ST37 (galvanized DIN EN 12329 – Fe//Zn12//A, and painted)

4

## Use

The group of MFL are very popular among the vibration dampers. They are easy to install.

## MFL adjustable machine feet

1 2 3 4  
MFL-01 NK 70 +/-5 SH A, ST37

1	Item code
2	Elastomer
3	Hardness
4	Metal quality