



- Galvanized
- Stainless
- 40 - +80 °C
- RoHS

1

Item code	d ₁	h	d ₂	Load [daN]
KA-01	80	25 - 35	M10	300
KA-090	90	35 - 45	M12	400
TF-1200	108	25 - 30	M16	500
KA-015	120	35 - 47	M12	600
KA-02	150	40 - 52	M16	1 000
KA-03	200	45 - 60	M20	3 000

Appearance	
<ul style="list-style-type: none"> • Elastomer (default natural rubber, NK) <ul style="list-style-type: none"> - Operation temperature -40 - +80 °C - Should not be used at oil, alkaline, acid - You can find other opportunities at the Elastomer 	2
<ul style="list-style-type: none"> • Hardness (default 70 +/-5 Shore A) <ul style="list-style-type: none"> - 40 (soft) - 55 (medium) - 70 (hard) 	3
<ul style="list-style-type: none"> • Metal insert <ul style="list-style-type: none"> - ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A) 	4

Use
The group of KA are very popular among the vibration dampers. They are easy to install.

KA adjustable machine feet	
1 2 3 4	
KA-01 NK 55 +/-5 SH A, ST37	
	1 Item code 2 Elastomer 3 Hardness 4 Metal quality