



- Galvanized
- Stainless
- 40 - +80 °C
- RoHS

1

Item code	d ₁	d ₂	d ₃	l ₁	l ₂
TF-1	M3	6,6	9	9	3
TF-2	M4	8,5	12	12	3,2
TF-3	M5	10,2	15	14,5	3,5
TF-4	M6	12,7	18	17	4,3
TF-5	M8	16	24	22	5,3

Appearance

- Elastomer (default natural rubber, NK)**
 - Operation temperature -40 - +80 °C
 - Should not be used at oil, alkaline, acid
 - You can find other opportunities at the Elastomer
- Hardness (default 55 +/-5 Shore A)**
 - 40 (soft)
 - 55 (medium)
 - 70 (hard)
- Metal insert**
 - ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)
 - A2 (stainless, AISI 304)
 - A4 (stainless, AISI 316)
 - MS (brass)

Use

The TF products are used to press thin plates for one side. When you tightened the screw, the nut front of the cylinder is bulge so it makes a flexible connection between the to parts.

TH-Flexible locator anti-vibration mount

1 2 3 4
TF-1 NK 55 +/-5 SH A, ST37

1	Item code
2	Elastomer
3	Hardness
4	Mental quality