



Galvanized

Stainless

-40 - +80 °C

RoHS

1

| Item code | d_1 | d_2 | d_3 | l_1 | l_2 |
|-----------|-------|-------|-------|-------|-------|
| TB-1 | 27,7 | 20,6 | 10 | 5,6 | 17,5 |
| TB-2 | 44,5 | 31,5 | 13 | 10,4 | 25,4 |
| TB-3 | 50,8 | 34,3 | 13 | 13,5 | 35 |
| TB-4 | 63,5 | 41,1 | 16 | 15,7 | 44,5 |
| TB-5 | 64 | 38 | 16 | 16 | 23 |
| TB-6 | 95 | 56,6 | 20 | 25,4 | 50,8 |

Appearance

- Elastomer (default natural rubber, NK)**
 - Operation temperature -40 - +80 °C
 - Should not be used at oil, alkaline, acid
 - You can find other opportunities at the Elastomer

2

- Hardness (default 55 +/-5 Shore A)**
 - 40 (soft)
 - 55 (medium)
 - 70 (hard)

3

- Metal insert**
 - ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)
 - A2 (stainless, AISI 304)

4

Use

Perfect for absorbing vibration generated by pumps, fans, washing machines, electric engines, control cabinets and other industrial and agricultural equipments.

Advantages: easy to assemble, high flexibility, economy, longevity.

T-BLOCK rubber vibration dampers

TB-1 NK 55 +/-5 SH A, ST37

1 Item code

2 Elastomer

3 Hardness

4 Metal quality