



Phosphated

Grinded

-40 - +80 °C

RoHS

1

Item code	d ₁	d ₂	l ₁	l ₂
ST1022-2024	22	10	20	24
ST1024-1518	24	10	15	18
ST1225-5054	25	12	50	54
ST1126-3236	26	11	32	36
ST1226-3236	26	12	32	36
ST1030-2430	30	10	24	30
ST1430-3842	30	14	38	42
ST1630-2933	30	16	29	33
ST1632-1617	32	16	16	17
ST1633-5058	33	16	50	58
ST1834-3642	34	18	36	42
ST1535-4550	35	15	45	50
ST1438-7381	38	14	73	81
ST2038-3538	38	20	35	38
ST2540-2020	40	25	20	20
ST2540-3030	40	25	30	30
ST2540-3540	40	25	35	40
ST1941-2533	41	19	25	33
ST2045-3540	45	20	35	40
ST2045-4043	45	20	40	43
ST2045-5962	45	20	59,5	62,5
ST2045-7075	45	20	70	75
ST1848-7891	48	18	78	91
ST2448-8593	48	24	85	93

Item code	d ₁	d ₂	l ₁	l ₂
ST2848-5055	48	28	50	55
ST2049-6063	49	20	60	63
ST2050-4046	50	20	40	46
ST2550-4045	50	25	40	45
ST2550-4550	50	25	45	50
ST2056-105110	56	20	105	110
ST3556-5055	56	35	50	55
ST1560-2030	60	15	20	30
ST2860-7275	60	28	72	75
ST3060-4555	60	30	45	55
ST2560-7682	60,3	25,6	76,5	82,5
ST3670-6065	70	36	60	65
ST3670-8590	70	36	85	90
ST4075-8088	75	40	80	88
ST4575-90100	75	45	90	100
ST5078-6066	78	50	60	66
ST5278-6565	78	52	65	65
ST4580-4545	80	45	45	45
ST4580-4550	80	45	45	50
ST5080-100110	80	50	100	110
ST2886-7785	86	28	77	85
ST5095-110120	95	50	110	120
ST42100-7075	100	42	70	75
ST50100-146159	100	50	146	159

Appearance

- **Elastomer (default natural rubber, NK)**
 - Operation temperature -40 - +80 °C
 - Should not be used at oil, alkaline, acid
 - You can find other opportunities at the Elastomer

2

- **Hardness (default 60 +/-5 Shore A)**

- 43 (soft)
- 60 (medium)
- 72 (hard)

3

- **Metal insert**

- ST37 (galvanized, phosphated or natural)

4

Use

The silentblocks are very useful in the industrial field. They ensure the flexible support for the different axis parts. You can find the frequently used parts among our products.

Silentblock

1 2 3 4
ST5095-110120 NK 60 +/-5 SH A, ST37

1	Product group
2	Elastomer
3	Hardness
4	Metal quality

